

MU-408 ColorFill

Instant mortar for tile gap filler that easy to clean, high color variety, not easily cracked. Suitable for gap filler of porous tile, granite tile, and mosaic on wall and floor.



Technical Data Sheet

Issued on : 2023 March 9

TECHNICAL DATA

Fresh density	1,87 Kg/l
Pot Life @35°C	60 minutes
Abrasive Resistance	850 mm ³ (ENI2808-2)
Compressive Strength	17 N/mm ² (ENI2808-3)
Shrinkage	2,36 mm/m
Packaging Size	1 Kg
Water addition	330-340 ml / 1 Kg
Grout width	1,0 - 4,0 mm

Consumption ColorFill

Tile Dimension	1 mm	2 mm	3 mm
30 cm x 30 cm x 6 mm	13.70	6.80	4.60
40 cm x 40 cm x 6 mm	18.20	9.10	6.10
60 cm x 60 cm x 10 mm	16.40	8.20	5.50
80 cm x 80 cm x 12 mm	18.20	9.10	6.10

Kemasan

Plastic 1 kg

Shelf life

10 months if it is stored inside the sealed bag and in the closed and dry room.

Product advantages

- Easy to clean
- Many color to choose to suite with your area
- High abrasive resistance
- High adhesion strength, crack resistance
- Easy to apply
- Nat width 1,0 - 4,0 mm

APPLICATION METHOD

1. Preparation application area

- Prepare the gap of porous tile, granite tile, or natural stone that will be applied using MU-408, clean from dust and other debris.
- Make sure the porous tile, granite tile and natural stone is strong and not loosen.

2. Mixing and blending process

- Pour the water as needed into container, and then pour MU-408.
- Mix evenly until it reaches homogeneous state.
- Wait approximately 2 minutes for a better outcome.

3. Application process

- Apply MU-408 into the gap between porous tile, granite tile, or natural stone.
- Wait for a while and clean using sponge or cloth.

SAINT-GOBAIN INDONESIA

Sequis Tower Level 15, Jl. Jend. Sudirman Kav. 71, RT.5/RW.3,

Senayan, Kebayoran Baru, Jakarta Selatan 12190

Office: 021-27099600

Email: CS.Indonesia@saint-gobain.com

Website: mortartutama.com | LinkedIn: Saint-Gobain Indonesia

ISO 9001:2015 Certified
ISO 14001:2015 Certified
ISO 45001:2018 Certified

